




Model 310 Type III



#### Dimensions

13.94" length

11.69" width

5.53" depth

#### Materials

Acrylic:

Clear

Polycarbonate with UvaLex®:

Clear

#### General Description

This unique ovate shaped refractor is suitable for commercial and residential roadway lighting.

#### Features and Benefits

- Rated up to 250watts
- Available in Type I which provides street lighting, Type II which provides roadway and street lighting, and Type III which provides roadway and parking area lighting.
- Model 310 is molded of UV stabilized Clear Acrylic for high efficiency in general lighting applications.
- Model 320 is molded with Clear Polycarbonate with or without UvaLex® for areas where breakage and high ambient heat are concerns.

#### Applications

Can be used with an ovate luminaire reflector. Compatible with HID and LED lamp sources.

Before final installation, dissipate static on parts by spraying with de-staticized air or by wiping with a clean, damp rag. This will help minimize dust build up.

#### Service Life

The service life of acrylic refractors is virtually unlimited when used within the recommended temperature limit. Polycarbonate refractors are subject to yellowing especially when used with high ultraviolet output light sources; this effect is enhanced at high temperatures.


#### Ordering Information

Please call 877-257-5841 for pricing and delivery.

### Type II Fixture Performance for Reference Only

**Report Number:** ITL37249  
**Total Luminaire Efficiency:** 79.83%  
**IES Classification:** Medium, Non-cutoff, Type II  
**Arc Tube Voltage Rise:** 2.8

Tested in accordance with IES standards.  
 Photometry based on a 150W HPS lamp.



#### Materials

See the LexaLite® brand price list for current part numbers and material offerings. Up-to-date and detailed material specifications can be found in the Resources section on our website [www.alpadvantage.com](http://www.alpadvantage.com).


When using acrylic, the surface temperature of the lens should not exceed 80°C. When using polycarbonate, the surface temperature of the lens should not exceed 90°C.

UvaLex® is LexaLite's proprietary treatment to retard yellowing in ultraviolet environments and is standard on these polycarbonate refractors.

#### Notice

A.L.P. assumes no responsibility for suitability of these materials in any luminaire or application. Please test for fit and function prior to ordering project quantities.

While A.L.P. utilizes IESNA testing procedures and believes our testing results to be accurate, A.L.P. provides photometry for reference only. Actual results will vary based on the actual light source(s) and power source(s) used, i.e. ballast, driver generator, etc. and the combinations in which they are used, as well as operating temperatures, and other electrical and environmental variables. We urge that customers perform their own fixture qualifications prior to making performance based claims. In no event will A.L.P. be liable for any loss, damage, including without limitation, indirect or consequential loss or damage in connection with the use of this information.



*This drawing is for reference only. Actual part dimensions will vary. Customer is urged to review actual samples to confirm fit and function. All specifications and dimensions are subject to change without notice.*